Cassette 1000 retail

Optimyst®

Picture the perfect fireplace. But forget about venting and heat, because flames are made of pure water vapour and LED light. Flames you can reach out and touch. The revolutionary Optimyst® Cassette models redefine the electric fireplace and enable you to add a dramatic fire feature to any space, with stunning realism. Ready to be combined and linked with a Cassette 500. For that see-through, three-sided, or fully open concept you envisage - in any length, for any location. Possibilities are simply endless. The perfect opportunity to play with fire!

USP's


- Suitable for installation projects and designed to fit into a custom-made frame or fireplace
- Easy-fill water tank, offers around 8-10 hours of continuous operation before refilling is required
- Quick-fit IEC (kettle) connection for an individual fireplace of any length
- Crackling logs sound effects with adjustable volume
- Log set available as an accessory




Article number: 210661 | EAN Code: 5011139210661 | Optimyst®








MODEL	DIM 'A'
CAS500	508mm
CAS1000	1017mm





All cassettes must have adequate ventilation for an optimal fire experience. For advice, read the manuals or visit the website www.dimplex-fires.eu

		Cassette 1000 retail
General specifications	Fire system	Optimyst [®]
	Article number	210661
	EAN code	5011139210661
	Model	Cassette series
	View of the fire	4 sided
	Colour	Black
	Decoration / fuel bed	Metal plate (optional LED log set available, 2x log set 500)
Product size	Measurements view of the fire (WxH)	99 x 20 cm
	Outside dimensions WxHxD	101 x 30 x 20 cm
Features	Heat output	No
	Thermostat	No
	Remote control	Yes
	Manual controlling directly at the fireplace possible yes / no	Yes
	Light module	LED
	Sound module	Yes
	Colour effects settings	No
Power consumption	Heat setting 1 in W	
	Heat setting 2 in W	-
	Flame only operation in W	450W
	Max. consumption	450W
Voltage	Voltage/Electrical frequency	230V/50Hz
Specifications	Product weight in kg	17,5
	Length of the cord	1,5 m
	Warranty	2 year